


DG SE PV SCI 1500 FM (952 566)


- Prewired modular complete unit for use in photovoltaic systems consisting of a base part and plug-in protection modules
- Combined disconnection and short-circuiting device with safe electrical isolation in the protection module (patented SCI principle)
- Integrated d.c. fuse allows safe replacement of protection modules without arc formation



Figure without obligation



Basic circuit diagram DG SE PV SCI 1500 FM



Dimension drawing DG SE PV SCI 1500 FM

Modular single-pole surge arrester with three-step d.c. switching device for PV systems with remote signalling contact for monitoring device (floating changeover contact).

Type	DG SE PV SCI 1500 FM
Part No.	952 566
SPD according to EN 50539-11	type 2
Max. PV voltage (U_{CPV})	1500 V
Short-circuit current rating (I_{SCP})	10 kA
Nominal discharge current (8/20 μ s) [(DC+/DC-) \rightarrow PE] (I_n)	12.5 kA
Voltage protection level (U_P)	≤ 6 kV
Response time (t_A)	≤ 25 ns
Operating temperature range (T_U)	-40 °C ... +80 °C
Operating state / fault indication	green / red
Number of ports	1
Cross-sectional area (min.)	1.5 mm ² solid / flexible
Cross-sectional area (max.)	35 mm ² stranded / 25 mm ² flexible
For mounting on	35 mm DIN rails acc. to EN 60715
Enclosure material	thermoplastic, red, UL 94 V-0
Place of installation	indoor installation
Degree of protection	IP 20
Capacity	3 module(s), DIN 43880
Approvals	KEMA, UL
Type of remote signalling contact	changeover contact
Switching capacity (a.c.)	250 V / 0.5 A
Switching capacity (d.c.)	250 V / 0.1 A, 125 V / 0.2 A, 75 V / 0.5 A
Cross-sectional area for remote signalling terminals	max. 1.5 mm ² solid / flexible
Weight	341 g
Customs tariff number	85363030
GTIN	4013364149090
PU	1 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.